



REQUEST FOR PROPOSALS

Class 5 Aircraft Rescue and Fire Fighting (ARFF) Vehicle

REQUEST NUMBER: 2312

DUE DATE: April 6, 2023

DUE TIME: 2:00 pm (local)

Contents

INTRODUCTION	2
SOLICITATION AND PROJECT SCHEDULE	2
VEHICLE SPECIFICATIONS.....	2
EQUIVALENT PRODUCT	3
REQUESTS FOR INFORMATION.....	3
SUBMISSION FORMAT AND EVALUATION CRITERIA	3
REQUEST FOR PROPOSAL SUBMISSION	4
TERMS AND CONDITIONS	5
MICHIGAN FREEDOM OF INFORMATION ACT	6
EVALUATION, STATUS UPDATES/AWARD NOTIFICATION	7
EXHIBITS	8
Exhibit A – FAA Class 5 ARFF Vehicle Specifications	8
Exhibit B – Federal Provisions	9

INTRODUCTION

The Gerald R. Ford International Airport Authority (GFIAA) is requesting proposals for the supply of an FAA Class 5 Aircraft Rescue and Fire Fighting (ARFF) vehicle. The ARFF vehicle is intended to carry rescue and firefighting equipment for the purpose of rescuing aircraft passengers, preventing aircraft fire loss, and combating fires in aircraft.

Proposed vehicles must be capable of providing 3000–4500-gallon water/Aqueous Film Forming Foam (AFFF) fire suppression, with the option of an additional supply of a 500 lb. sodium-based dry chemical as a complimentary system only.

The Gerald R. Ford International Airport is the second busiest airport in Michigan, serving business and leisure travelers with nonstop and connecting flights on six airlines. The Ford Airport is managed and operated by the Gerald R. Ford International Airport Authority.

SOLICITATION AND PROJECT SCHEDULE

ACTIVITY	DATE
RFP Issue Date	March 10, 2023
Question Deadline	March 28, 2023
Submission Due Date	April 6, 2023 at 2 pm

GFIAA reserves the right to modify the deadline set forth in the above table in its sole discretion. Any such modifications will be stated in an addendum.

VEHICLE SPECIFICATIONS

Proposals must comply with the provided specifications for a Class 5 Aircraft Rescue and Fire Fighting Vehicle listed in Exhibit A of this solicitation document.

In addition to the provided specifications, proposals must also include:

- Ability to accommodate GFIAA branding and uniformity with existing fleet paint schemes.
- Conforming to FAA funding requirements (listed below)

EQUIVALENT PRODUCT

Proposals will be accepted for consideration on any make or model that is equal or superior to the specifications provided. Decisions of equivalency and suitability will be at the sole interpretation of GFIA. A blanket statement that equipment proposed will meet all requirements will not be sufficient to establish equivalence. An original detailed manufacturer's brochure of the proposed product is to be submitted.

REQUESTS FOR INFORMATION

Questions regarding this solicitation are to be submitted in writing to purchasing@grr.org prior to 2 p.m. on March 28, 2023.

GFIAA reserves the right to publish and respond to an inquiry, respond directly to the inquirer without publishing or not respond to the inquiry at its sole discretion. Unless otherwise indicated, all questions will be compiled into one document and answers will be issued as a Questions & Answers document within 4 days after the question deadline.

It is the firm's responsibility to become familiar with and fully informed regarding the terms, conditions, and specifications of this solicitation. Lack of understanding or misinterpretation of any portions of this solicitation shall not be cause for withdrawal after opening or for subsequent protest of award.

Addendums will only be published by the GFIAA Purchasing Department and available for review at www.grr.org.

SUBMISSION FORMAT AND EVALUATION CRITERIA

Submissions should include and will be evaluated on the elements outlined below:

Executive Summary – One (1) page maximum

Summarize the Respondent's strong points and how experience, particularly with similar responsibilities, will benefit the stakeholders.

Business Organization – One (1) page maximum

State the full name and address of the organization and, if applicable, the branch office, consultants, or other subordinate elements that will provide or assist in providing the service. **Include phone number(s), email address(s)** and Respondent's website address.

Product Recommendation – Twelve (12) pages maximum

State in succinct terms the Respondent's understanding of the major issues of this request and propose a product with specifications that can fully fulfil the requirements listed within this RFP. Provide any alternative suggestion of equipment or any additional add ons to your main proposal that may prove beneficial to the GFIAA to consider as well. Describe product delivery timeframe.

Warranty and Maintenance Information – No page limit

Provide a detailed description of all relevant warranty information. Include duration, coverage, limits, etc. Include supporting documentation where required. List any requirements regarding who and where maintenance may be performed in compliance with the specified warranty information.

References – One (1) page maximum

Provide a minimum of three (3) relevant references, preferably for projects of similar scope and complexity. Include the names of the projects, location, completion date, project cost, and specific challenges; identify project team members and references for each project including telephone numbers and email addresses.

Fee Proposal and Delivery – Two (2) pages maximum

Provide a detailed cost proposal, including delivery and lead times.

REQUEST FOR PROPOSAL SUBMISSION

Responses may be delivered physically or electronically. To be considered, complete submissions must be received prior to the due date and time specified (local time).

- Hard copy responses can be mailed or otherwise delivered to the address below.

Submission address:

Attn: AJ Nye, Procurement Specialist

Gerald R Ford International Airport Authority

5500 44th St SE

Grand Rapids, MI 49512

- Electronic responses can be securely uploaded as a single pdf document to:

<https://www.dropbox.com/request/g1HscZBOO07PRoiyhM7Y>

Electronic submissions shall be named with a form or portion of the firm's name as part of the document name.

The firm certifies the response submitted has not been made or prepared in collusion with any other respondent and the prices, terms or conditions thereof have not been communicated by or on behalf of the respondent to any other respondent prior to the official opening of this request. This certification may be treated for all purposes as if it were a sworn statement made under oath, subject to the penalties for perjury. Moreover, it is made subject to the provisions of 18 U.S.C. Section 1001, relating to the making of false statements.

Submissions may be withdrawn by written request only if the request is received on or before the opening date and time.

Submissions not meeting these criteria may be deemed non-responsive.

GFIAA is not liable for any costs incurred by any prospective firm prior to the awarding of a contract, including any costs incurred in addressing this solicitation.

TERMS AND CONDITIONS

GFIAA reserves the right to require that its standard terms and conditions apply to any actual order placed in response to a firm's submission. No attempt to modify GFIAA's Standard Terms and Conditions shall be binding, absent agreement on such modification in writing and signed by GFIAA.

No payment shall be made to the Respondent for any extra material or services, or of any greater amount of money than stipulated to be paid in the contract, unless changes in or additions to the contract requiring additional outlay by the Respondent shall first have been expressly authorized and ordered in writing by contract amendment or otherwise furnished by the GFIAA.

The intent of these specifications is to solicit a properly designed and all-inclusive response. Any requirements not in the specifications, but which are needed for such a response, are to be included in the submission.

The Gerald R Ford International Airport Authority, in accordance with the provisions of Title VI of the Civil Rights Act of 1964 (78 Stat. 252, 42 U.S.C. §§ 2000d to 2000d-4) and the Regulations, hereby notifies all bidders that it will affirmatively ensure that for any contract entered into pursuant to this advertisement, disadvantaged business enterprises and airport concession disadvantaged business enterprises will be afforded full and fair opportunity to submit bids in response to this invitation and will not be discriminated against on the grounds of race, color, or national origin in consideration for an award.

The Respondent shall not discriminate against an employee or applicant for employment with respect to hire, tenure, terms, conditions or privileges of employment, or a matter directly or indirectly related to employment, because of race, color, religion, national origin, age, sex, height, weight, marital status, or disability that is unrelated to the individual's ability to perform the duties of a particular job or position.

The Respondent shall observe and comply with all applicable federal, state, and local laws, ordinances, rules and regulations at all times during the completion of any contract with the GFIAA.

The terms of this request shall be interpreted, construed, and enforced pursuant to the laws of the State of Michigan, and the Parties irrevocably consent to the jurisdiction of the federal and state courts presiding in Michigan.

The GFIAA is tax-exempt, and a regional airport authority organized under 2015 P.A. 95, being MCL 259.137 et. seq.

Vendor Representation and Warranty Regarding Federal Excluded Parties List: The Respondent acknowledges that the GFIAA may be receiving funds from or through the Federal Government; such funds may not be used to pay any Respondent on the Federal Excluded Parties List (EPLS). The Respondent represents and warrants to the GFIAA that it

is not on the Federal EPLS. If the Respondent is in non-compliance at any time during execution or term of this agreement (including any extensions thereof), the Respondent shall be in breach and the GFIAA shall be entitled to all remedies available to it at law or equity, specifically including but not limited to recovery of all moneys paid to the Respondent, all consequential damages (including the loss of grant funding or the requirement that grant funding be returned), and attorney fees (including the costs of in-house counsel) sustained as a result of the Respondent's non-compliance with this warranty and representation.

Pursuant to the Michigan Iran Economic Sanctions Act, 2012 P.A. 517, by submitting a bid, proposal or response, Respondent certifies, under civil penalty for false certification, that it is fully eligible to do so under law and that it is not an "Iran linked business," as that term is defined in the Act.

Insurance requirements are posted on the Documents and Forms page of the GFIAA website within the Purchasing Terms and Conditions document.

Termination For Cause: Should the firm fail to perform the Work as required by and in accordance with the schedule or time requirements, or otherwise violate any of the terms set forth in the Solicitation Request, it shall constitute breach of the Contract. Other than in force majeure situations, Respondent shall have five (5) calendar days to cure a breach of the Contract (the "Cure Period") following issuance of GFIAA written notice. Failure to cure a breach of the Contract within said Cure Period shall allow the GFIAA to, without further notice to the Respondent, declare the Contract terminated and proceed with the replacement of the Respondent and the GFIAA shall be entitled to all remedies available to it at law or in equity including a claim against any required payment/performance bonds.

Termination Without Cause: Notwithstanding any other provision, at any time and without cause, GFIAA shall have the right, in its sole discretion, to terminate the contract by giving sixty (60) days written notice.

Although it is the intent to contract with one provider, the GFIAA reserves the right to contract with alternate sources if the Respondent is unable or unwilling to service its obligation, or it is deemed by GFIAA to be in its best interest to use alternate sources.

Assignment: Neither party shall assign or delegate any of its rights or obligations under this Agreement without the prior written consent of the other party.

Respondent warrants that they are an authorized provider of products or services of his/her submission.

MICHIGAN FREEDOM OF INFORMATION ACT

Information submitted in this solicitation is subject to the Michigan Freedom of Information Act and may not be held in confidence after the Respondent's submission is opened. A submission will be available for review after the project has been awarded.

GFIAA cannot assure that all of the information submitted as part of or peripheral to the Respondent's submission will be kept confidential. Any Respondent submission language designated as confidential is considered automatically invalid and void. GFIAA is subject to the Michigan Freedom of Information Act, which prohibits it from concealing information on or associated with responses, successful or unsuccessful, once they are opened.

EVALUATION, STATUS UPDATES/AWARD NOTIFICATION

The Authority reserves the right to request additional information it may deem necessary after the submissions are received.

As part of the evaluation process, Respondents may be requested to make an oral presentation, at the Respondent's expense, to an evaluation committee. Key staff to be assigned to this project must participate in this presentation unless otherwise waived by the Authority. The presentation may be followed by a question-and-answer session.

The Authority reserves the right at its discretion to waive irregularities of this solicitation process.

In the event of extension errors, the unit price shall prevail and the Respondent's total offer will be corrected accordingly. In the event of addition errors, the extended totals will prevail and the Respondent's total will be corrected accordingly. Respondent must check their submission where applicable. Failure to do so will be at the Respondent's risk. Submissions having erasures or corrections must be initialed in ink by the Respondent. Respondents are cautioned to recheck their submissions for possible errors.

The Respondent shall not be allowed to take advantage of error, omissions or discrepancies in the specifications.

The Authority, at its sole discretion, reserves the right to award to the Respondent whose response is deemed most advantageous to the Authority. The Authority, at its sole discretion, shall select the most responsive and responsible Respondent and evaluate all responses based on the requirements and criterion set forth in this solicitation while reserving the right to weigh specifications and other factors in the award. The Authority reserves the right to reject any and all submissions as a result of this solicitation.

The Authority reserves the right to award by line item when applicable and to accept or reject any or all parts of a submission.

Accelerated discounts should be so stated at the time of submission. If quick-pay discounts are offered, The Authority reserves the right to include that discount as part of the award criterion. Prices must, however, be based upon payment in thirty (30) days after receipt, inspection, and acceptance. In all cases, quick-pay discounts will be calculated from the date of the invoice or the date of acceptance, whichever is later.

Award notifications are posted on the Authority website. It is the Respondent's responsibility to monitor the website for status updates.

EXHIBITS

Exhibit A – FAA Class 5 ARFF Vehicle Specifications

See next page

3.5. VEHICLE PROCUREMENT SPECIFICATION, CLASS 5

PROCUREMENT SPECIFICATION

Class 5

AIRCRAFT RESCUE AND FIRE FIGHTING (ARFF) VEHICLE

1. SCOPE. This Procurement Specification (PS) covers a commercially produced diesel engine driven ARFF vehicle for an Index D airport. It includes a 3000-4500 gallon water/Aqueous Film Forming Foam (AFFF) fire suppression system: 500 lb sodium-based dry chemical only complementary system.

The ARFF vehicle is intended to carry rescue and fire fighting equipment for the purpose of rescuing aircraft passengers, preventing aircraft fire loss, and combating fires in aircraft.

2. CLASSIFICATION. The ARFF vehicle(s) covered by this PS are classified in accordance with Part 139, Certification and Operations: Land Airports Serving Certain Air Carriers, Section 315, Aircraft Rescue and Firefighting: Index Determination; Section 317, Aircraft Rescue and Firefighting: Equipment and Agents; and Federal Aviation Administration (FAA) Advisory Circular (AC) 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles, as follows:

Airport Index	Vehicle Class	Minimum Rated Capacities (gallons/liters)
Index D	5	3000 gallon/11,356 liter water/AFFF solution
Index D	5	3500 gallon/13,249 liter water/AFFF solution
Index D	5	4000 gallon/15,142 liter water/AFFF solution
Index D	5	4500 gallon/17,034 liter water/AFFF solution

3. VEHICLE CONFORMANCE/PERFORMANCE CHARACTERISTICS. The ARFF vehicle will be in accordance with the applicable requirements of National Fire Protection Association (NFPA) 414, Standard for Aircraft Rescue and Fire Fighting Vehicles (2007 Edition), and AC 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles.

3.1 General Administration Requirements.

3.1.1 Manuals. Technical manuals will consist of operator, service, and parts manuals. All manuals are required to be provided in hardcopy and in digital format on CDs when requested.

3.1.1.1 Technical manuals. The overall format for the manuals will be commercial. Each technical manual will have a title page. Line art will be used to the maximum extent possible for illustrations and parts lists. One complete set of engine and transmission parts, service and operator's manuals will be packed with each vehicle.

- a. The contractor will provide digitized manuals in CD format when requested in addition to or in place of printed paper copies.

- b. The contractor will provide two complete sets of hardcopy manuals and / or CDs when requested.

3.1.1.1.1 Operator's manual. The operator's manual will include all information required for the safe and efficient operation of the vehicle, including fire extinguishing systems, equipment, and any special attachments or auxiliary support equipment. As a minimum, the operator's manual will include the following:

- a. The location and function of all controls and instruments will be illustrated and functionally described.
- b. Safety information that is consistent with the safety standards established by the Occupational Safety and Health Administration (OSHA) and NFPA.
- c. All operational and inspection checks and adjustments in preparation for placing the vehicle into service upon receipt from the manufacturer.
- d. Tie down procedures for transport on a low-boy trailer.
- e. Warranty information and the period of the warranty coverage for the complete vehicle and for any component warranty that exceeds the warranty of the complete vehicle. Addresses and telephone numbers will be provided for all warranty providers.
- f. General description and necessary step-by-step instructions for the operation of the vehicle and its fire extinguishing system(s) and auxiliary equipment.
- g. A description of the post-operational procedures (draining, flushing, re-servicing, et cetera).
- h. Daily maintenance inspection checklists that the operator is expected to perform, including basic troubleshooting procedures.
- i. Disabled vehicle towing procedures.
- j. Procedures and equipment required for changing a tire.
- k. Schedules (hours, miles, time periods) for required preventative maintenance and required periodic maintenance.
- l. Line art drawing of the vehicle, including panoramic views (front, rear, left, and right sides) showing basic dimensions and weights (total vehicle and individual axle weight for the unloaded and fully loaded vehicle). For the purposes of this AC, "unloaded" is defined as a lack of agent, occupants and compartment load, and "loaded" is defined as including agent, occupants and compartment load.

3.1.1.1.2 Service manual. The service manual will identify all special tools and test equipment required to perform servicing, inspection, and testing. The manual will cover

troubleshooting and maintenance as well as minor and major repair procedures. The text will contain performance specifications, tolerances, and fluid capacities; current, voltage, and resistance data; test procedures; and illustrations and exploded views as may be required to permit proper maintenance by qualified vehicle mechanics. The manual will contain an alphabetical subject index as well as a table of contents. The service manual will contain at least the following, where applicable:

- a. Fire fighting system schematic(s).
- b. Hydraulic schematic.
- c. Pneumatic schematic.
- d. Electrical schematic.
- e. Winterization schematic.
- f. Fuel schematic.
- g. Schedules for required preventative maintenance and required periodic maintenance.
- h. Lubrication locations, procedures, and intervals for parts of the vehicle and equipment that require lubrication.

3.1.1.1.3 Parts identification manual. The parts manual will include illustrations or exploded views (as needed) to identify properly all parts, assemblies, subassemblies, and special equipment. All components of assemblies shown in illustrations or exploded views will be identified by reference numbers that correspond to the reference numbers in the parts lists. All purchased parts will be cross-referenced with the original equipment manufacturer's (OEM) name and part number. The parts identification manual will provide the description and quantity of each item used for each vehicle. The size, thread dimensions, torque specifications, and special characteristics will be provided for all nonstandard nuts, bolts, screws, washers, grease fittings, and similar items. The manual will contain a numerical index. The parts manual will contain a list of all of the component vendor names, addresses, and telephone numbers referenced in the parts list.

3.1.2 Painting, plating, and corrosion control.

3.1.2.1 Finish. Exterior surfaces will be prepared, primed, and painted in accordance with all of the paint manufacturer's instructions and recommendations. Vehicles will be painted and marked in accordance with AC 150/5210-5, Painting, Marking, and Lighting of Vehicles Used on an Airport. The interior finish of all compartments will be based on the manufacturer's standard production practice. This may include painting, texturing, coating or machine swirling as determined by the manufacturer. All bright metal and anodized parts, such as mirrors, horns, light bezels, tread plates, and roll-up compartment doors, will not be painted. All other surfaces capable of being painted must be in the appropriate yellow-green color.

3.1.2.2 Dissimilar metals. Dissimilar metals, as defined in MIL-STD-889, Dissimilar Metals, will not be in contact with each other. Metal plating or metal spraying of dissimilar base metals to provide electromotively compatible abutting surfaces is acceptable. The use of dissimilar metals separated by suitable insulating material is permitted, except in systems where bridging of insulation materials by an electrically conductive fluid can occur.

3.1.2.3 Protection against deterioration. Materials that deteriorate when exposed to sunlight, weather, or operational conditions normally encountered during service will not be used or will have a means of protection against such deterioration that does not prevent compliance with performance requirements. Protective coatings that chip, crack, or scale with age or extremes of climatic conditions or when exposed to heat will not be used.

3.1.2.4 Reflective stripes. A minimum eight (8) inch horizontal band of high gloss white paint or white reflective tape (Retroreflective, ASTM-D 4956-09, *Standard Specification for Retroreflective Sheeting for Traffic Control*, TYPE III & above) must be applied around the vehicle's surface.

3.1.2.5 Lettering. The manufacturer will apply the airport's 'Name' and 'Insignia' (if available) in a contrasting color or by decal on both sides of the vehicle in long radius elliptical arches above and below the lettering center line. The size of the lettering will be a minimum of 2½-inches to a maximum of 6-inches. Reflective lettering is allowed if the material is the same as that which is used for the reflective stripe (as specified in AC 150/5210-5).

3.1.3 Vehicle identification plate. A permanently marked identification plate will be securely mounted at the driver's compartment. The identification plate will contain the following information:

- a. NOMENCLATURE
- b. MANUFACTURER'S MAKE AND MODEL
- c. MANUFACTURER'S SERIAL NUMBER
- d. VEHICLE CURB WEIGHT: kg (pounds)
- e. PAYLOAD, MAXIMUM: kg (pounds)
- f. GROSS VEHICLE WEIGHT (GVW): kg (pounds)
- g. FUEL CAPACITY AND TYPE: gals (gallons)
- h. DATE OF DELIVERY (month and year)
- i. WARRANTY (months and km (miles))
- j. CONTRACT NUMBER
- k. PAINT COLOR AND NUMBER

A second permanently marked information data plate will be securely mounted on the interior of the driver's compartment. The plate will contain the information required by NFPA 414, Standard for Aircraft Rescue and Fire Fighting Vehicles (2007 Edition), Section 1.3.5 Vehicle Information Data Plate. A single plate that combines or contains the information required for both plates is acceptable.

3.1.4 Environmental conditions.

3.1.4.1 Vehicle operation and storage temperature conditions will vary with geographical location. Thus, the locality temperature range can go from -40° to 110°F. Refer to NFPA 414 for vehicle winterization criteria.

3.1.4.2 Extreme temperature range. The vehicle will be capable of satisfactory storage and operation in temperatures ranging from -40° to 110°F. The vehicle will be equipped with a cab, chassis, and agent winterization system, permitting operation at -40°F. The winterization system will not detract from the performance of the vehicle or the firefighting system in ambient temperatures up to 110°F. The vehicle chassis winterization system will maintain the engine coolant, lubricants, fuel, and electrical systems operational at ambient temperatures of -40°F. The vehicle agent winterization system will provide sufficient insulation and heating capacity, by means of hot circulating liquids and/or forced air heat exchangers, to permit satisfactory operation of the vehicle and firefighting systems for a 2-hour period at ambient temperatures as low as -40° F with the vehicle fully operational and the engine running. At the end of this 2-hour period, the vehicle will be capable of successfully discharging its agents. All compartments not winterized will be marked as such on the interior of the compartment. The marking will state that the compartment is not winterized and cannot be used for the storage of items capable of freezing.

3.1.5 Reduction of potential foreign object damage. All loose metal parts, such as pins, will be securely attached to the vehicle with wire ropes or chains. Removable exterior access panels, if provided, will be attached with captive fasteners.

3.1.6 Vehicle Mobility.

3.1.6.1 Operating terrain. The vehicle will be capable of operating safely on paved roads, graded gravel roads, cross country terrain, and sandy soil environments. Cross country terrain consists of open fields, broken ground, and uneven terrain. An off-road, high-mobility suspension system resulting in no more than 0.5 G_{rms} acceleration at the driver's seat of the vehicle when traversing an 8-inch (20 cm) diameter half round at 35 mph (56 kph) must be provided. The suspension design by which the manufacturer meets the suspension performance requirements is at the manufacturer's discretion.

3.1.6.2 Gradeability. The fully loaded vehicle will be able to ascend any paved slope up to and including 50-percent.

3.1.6.3 Side slope stability. The fully loaded vehicle will be stable on a 30° side slope when tested in accordance with NFPA 414.

3.1.6.4 Cornering stability. The fully loaded vehicle will be stable in accordance with NFPA 414 when tested in accordance with NFPA 414.

3.2 Weights and dimensions.

3.2.1 Overall dimensions. The maximum dimensions listed below are desirable to ensure vehicles can be accommodated in existing fire stations. Likewise, the overall dimensions should be held to a minimum that is consistent with the best operational performance of the vehicle and the design concepts needed to achieve this performance and to provide maximum maneuverability in accordance with NFPA 414.

Vehicle Capacity /Dimensions	3000 Gallon	4500 Gallon
Length (inches/cm)	480/1219	540/1372
Width (inches/cm, excluding mirrors)	124/315	122/310
Height (inches/cm)	154/391	154/391

NOTE: For Airport Operator Validation: Consult AC 150/5210-15, Aircraft Rescue and Fire Fighting Station Building Design, Appendix A, to ensure vehicles measurements do not exceed existing airport fire station dimensions.

<u>VEHICLE MEASUREMENT VALIDATION</u>
Not applicable.
ADO/FAA Approval: ⇒ _____

3.2.2 Angles of approach and departure. The fully loaded vehicle will have angles of approach and departure of not less than 30°.

3.2.3 Field of vision. The vehicle will have a field of vision in accordance with NFPA 414.

3.2.3.1 Mirrors. Combination flat and convex outside rearview mirrors will be installed on each side of the cab. The flat mirrors will be of the motorized remote control type, providing not less than 60° horizontal rotational viewing range. The flat mirrors will also have electrically heated heads. Mirror remote and heating controls will be located on the instrument panel within reach of the seated driver. To provide the driver a clear view of the area ahead of the vehicle and to eliminate potential blind spots, a rectangular mirror will be installed on the lower corner of each side of the windshield, having a minimum area of 35 square inches. The vehicle will have a back-up (rear-view) camera with a display monitor mounted above the driver in the cab. Cameras and monitors that are designed to replace the function of the side-view mirrors are not an approved option in this specification.

3.3 Chassis and vehicle components.

3.3.1 Engine. The vehicle will have a turbocharged diesel engine that is certified to comply with the Environmental Protection Agency (EPA) and state laws for off-highway emission requirements at the time of manufacture. The engine and transmission must operate efficiently and without detrimental effect to any drive train components when lubricated with standard, commercially available lubricants according to the recommendations of the engine and transmission manufacturers.

3.3.1.1 Acceleration. The fully loaded vehicle will accelerate from 0 to 50 miles per hour (mph) on a level paved road within 35 seconds.

3.3.1.2 Maximum speed. The fully loaded vehicle will attain a minimum top speed of 70 mph on a level, paved road.

3.3.1.3 Pump and roll on a 40-percent grade. The fully loaded vehicle will be capable of pump and roll operations on a paved, dry, 40-percent grade in accordance with NFPA 414.

3.3.1.4 Altitude. Where justified, the vehicle, including the pumping system, will be designed for operation at 2,000 feet above sea level.

<u>JUSTIFICATION</u>
ADO/FAA Approval: ⇒ _____

3.3.2 Engine cooling system. The engine cooling system will be in accordance with NFPA 414. A label will be installed near the engine coolant reservoir reading "Engine Coolant Fill."

3.3.3 Fuel system. The fuel system will be in accordance with NFPA 414.

3.3.3.1 Fuel priming pump. The vehicle will be equipped with an electric or pneumatic fuel pump in addition to the mechanical fuel pump. The electric/pneumatic pump will be used as a priming pump capable of re-priming the engines fuel system.

3.3.3.2 Fuel tank. The vehicle will have one or two fuel tanks with a minimum usable capacity in accordance with NFPA 414, as amended by NFPA 414. Each tank will have a fill opening of 3 inches minimum, readily accessible to personnel standing on the ground and designed to prevent fuel splash while refueling. Each tank will be located and mounted so as to provide maximum protection from damage, exhaust heat, and ground fires. If more than one tank is furnished, means will be provided to assure equalized fuel level in both tanks. An overturn fuel valve will be provided for each tank to prevent spillage in the event of a rollover. Each fuel tank must be prominently labeled "Diesel Fuel Only".

3.3.4 Exhaust system. The exhaust system will be in accordance with NFPA 414. The exhaust system will be constructed of high grade rust resistant materials and protected from damage resulting from travel over rough terrain. The muffler(s) will be constructed of aluminized steel or stainless steel. Exhaust system outlet(s) will be directed upward or to the rear, away from personnel accessing equipment compartments and the engine air intake, and will not be directed toward the ground.

3.3.5 Transmission. A fully automatic transmission will be provided. The transmission will be in accordance with NFPA 414.

3.3.6 Driveline. The vehicle driveline will be in accordance with NFPA 414. If the driveline is equipped with a differential locking control, a warning/caution label will be placed in view of the driver indicating the proper differential locking/un-locking procedures. The operator's manual will also include a similar warning/caution. All moving parts requiring routine lubrication must have a means of providing for such lubrication. There must be no pressure lubrication fittings where their normal use would damage grease seals or other parts.

3.3.7 Axle capacity. Each axle will have a rated capacity, as established by the axle manufacturer, in accordance with NFPA 414.

3.3.8 Suspension. The suspension system will be in accordance with NFPA 414 and AC 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles.

3.3.9 Tires and wheels. Tires and wheels will be in accordance with NFPA 414. The vehicle will be equipped with single tires and wheels at all wheel positions. The vehicle will be equipped with tubeless steel belted radial tires with non-directional on/off-road type tread mounted on disc wheel assemblies. Tire and wheel assemblies will be identical at all positions. Tires and wheels will be certified by the manufacturer for not less than 25 miles of continuous operation at 60 mph at the normal operational inflation pressure. A spare tire and wheel assembly will be provided; however, the spare tire and wheel assembly are not required to be mounted on the vehicle. Tires will be new. Retreads, recaps, or re-grooved tires will not be permitted.

Tire bead locks, where justified, may be installed on all tires and rims.

JUSTIFICATION
Not Applicable
ADO/FAA Approval: ⇨ _____

3.3.10 Towing connections. The vehicle will be equipped with towing connections in accordance with NFPA 414. The vehicle will be designed for flat towing; the capability to lift and tow the vehicle is not required. The tow connections may intrude into the 30 degree approach angle.

3.3.11 Brake system. The vehicle will be equipped with a multi-channel all-wheel antilock brake system with at least one channel for each axle. The brakes will be automatic, self-adjusting and fully air-actuated. Brakes will be in accordance with CFR 49 CFR 393.40 through 393.42(b)), 393.43, and 393.43 through 393.52. The braking system, complete with all necessary components will include:

- a. Air compressor having a capacity of not less than 16 standard cubic feet per minute (scfm).
- b. Air storage reservoir(s), each tank equipped with drain (bleed) valves, and with safety and check valves between the compressor and the reservoir tank.
- c. Automatic moisture ejector on each air storage reservoir. Manual air tank drains are acceptable if they are labeled, are centrally located in one compartment and are accessible by an individual standing at the side of the vehicle.
- d. Automatic slack adjusters on cam brakes or internal self-adjusting brakes on wedge brakes on all axles.
- e. Spring set parking brakes.

All components of the braking system will be installed in such a manner as to provide adequate road clearance when traveling over uneven or rough terrain, including objects liable to strike and cause damage to the brake system components. No part of the braking system will extend below the bottom of wheel rims, to ensure, in case of a flat tire, that the weight of the vehicle will be supported by the rim and the flat tire and not be imposed on any component of the braking system. Slack adjusters and air chambers will be located above the bottom edge of the axle carrier.

3.3.11.1 Air dryer. A replaceable cartridge desiccant air dryer will be installed in the air brake system. The dryer will have the capability of removing not less than 95 percent of the

moisture in the air being dried. The dryer will have a filter to screen out oil and solid contaminants. The dryer will have an automatic self-cleaning cycle and a thermostatically controlled heater to prevent icing of the purge valve.

3.3.11.2 Compressed air shoreline or vehicle-mounted auxiliary air compressor. A flush mounted, check valved, auto-eject compressed air shoreline connection will be provided to maintain brake system pressure while the vehicle is not running. The shoreline will be flush mounted (not to extend outside the body line), located on the exterior of the vehicle, either on the left side rear corner of the cab, or at the rear of the vehicle. In lieu of a compressed air shoreline connection, the vehicle may be equipped with a 110 volt shoreline connected vehicle-mounted auxiliary air compressor. In lieu of a compressed air shoreline connection, the vehicle may be equipped with an electrical shoreline connected vehicle mounted auxiliary air compressor.

3.3.12 Steering. The vehicle will be equipped with power steering. Rear-wheel steering technology is not an approved vehicle option.

3.3.12.1 Steering effort. The steering system performance will be in accordance with NFPA 414.

3.3.12.2 Turning diameter. The fully loaded vehicle will have a wall to wall turning diameter of less than three times the overall length of the vehicle in both directions in accordance with NFPA 414.

3.3.13 License plate bracket. A lighted license plate bracket will be provided at the left rear and left front of the vehicle. The location of the left front bracket will be placed so as not to interfere with the operation of fire fighting systems.

3.4 Cab. The vehicle will have a fully enclosed two door cab of materials which are corrosion resistant, such as aluminum, stainless steel, or glass reinforced polyester construction. Steps and handrails will be provided for all crew doors, and at least one grab handle will be provided for each crew member, located inside the cab for use while the vehicle is in motion. The lowermost step(s) will be no more than 22 inches above level ground when the vehicle is fully loaded. A tilt and telescoping steering column will be provided.

3.4.1 Windshield and windows. The windshield and windows will be of tinted safety glass. Each door window will be capable of being opened far enough to facilitate emergency occupant escape in the event of a vehicle accident. The vehicle windows will have an electric control system.

3.4.2 Cab interior sound level. The maximum cab interior sound level will be in accordance with NFPA 414.

3.4.3 Instruments and controls. All instruments and controls will be illuminated and designed to prevent or produce windshield glare. Gauges will be provided for oil pressure, coolant temperature, and automatic transmission temperature. In addition to the instruments and controls required by NFPA 414, the following will be provided within convenient reach of the seated driver:

- a. Master warning light control switch,
- b. Work light switch(es), and
- c. Compartment "Door Open" warning light and intermittent alarm that sounds when a compartment door is open and the parking brakes are released or the transmission is in any position other than neutral.

3.4.4 Windshield deluge system. The vehicle will be equipped with a powered windshield deluge system. The deluge system will be supplied from the agent water tank and will have an independent pumping system. The deluge system activation switch will be located within reach of the seated driver and turret operator.

3.4.5 Forward Looking Infrared (FLIR). A forward looking infrared (FLIR) camera and in-cab monitor, meeting the requirements of NFPA 414, will be provided. In addition, the FLIR monitor described in NFPA 414 will have a minimum dimension of 10 in (25 cm) (measured diagonally) and be located in a position where it is visible to both the seated driver and turret operator.

3.4.6 Climate control system. The offeror/contractor's standard heater/defroster and air conditioning system will be provided. The climate control system will induct at least 60 cubic feet per minute of fresh air into the cab. Cab mounted components will be protected from inadvertent damage by personnel.

3.4.7 Seats. The driver seat will be adjustable fore and aft and for height. The turret operator's seat, located to the right front of the driver's seat, will be a fixed (non-suspension) type. Each seat will be provided with a Type 3 seat belt assembly (i.e., 3-point retractable restraint) in accordance with CFR 49 CFR 571.209. Seat belts must be of sufficient length to accommodate crew members in full Personal Protective Equipment (PPE).

3.4.7.1. Seat Options. Two types of seat options are allowed in the vehicle. A standard seat contains a hard/fixed back. For these seats, a remote-mounted bracket designed to store a Self-Contained Breathing Apparatus (SCBA) will be provided. The remote-mounted bracket for the driver and turret operator (at a minimum) must be placed inside the cab. The brackets for seat positions #3 and #4 may be placed outside of the cab if necessary. An SCBA seat, on the other hand, contains an opening which can accommodate someone wearing an SCBA. The chart below represents the user's stated preference for the vehicle seating configuration.

Position	Standard	SCBA-Seat	N/A
Driver	X		
Turret		X	
# 3			X
# 4			X

<u>JUSTIFICATION</u>
ADO/FAA Approval: ⇒ _____

3.4.8 Windshield wipers and washer. The vehicle will be equipped with electrically powered windshield wipers. The wiper arms and blades will be of sufficient length to clear the windshield area described by SAE J198, Windshield Wiper Systems - Trucks. Individual wiper controls will include a minimum of two speed settings and an intermittent setting. The wiper blades will automatically return to a park position, out of the line of vision. The vehicle will be equipped with a powered windshield washer system, including an electric fluid pump, a minimum one gallon fluid container, washer nozzles mounted to the wiper arms (wet arms), and a momentary switch.

3.4.9 Warning signs. Signs that state "Occupants must be seated and wearing a seat belt when apparatus is in motion" will be provided in locations that are visible from each seated position in accordance with NFPA 414."

3.4.10 Lateral accelerometer and/or stability control system. The vehicle will be equipped with a lateral accelerometer and/or an electronic stability control system in accordance with NFPA 414.

3.4.11 Monitoring and Data Acquisition System (MADAS). The vehicle will be equipped with a MADAS as prescribed by NFPA 414.

3.5 Body, compartments, and equipment mounting.

3.5.1 Body. The vehicle will have a corrosion-resistant body.

3.5.2 Compartments. The vehicle body will have lighted compartments in accordance with NFPA 414 with a minimum of 10 cubic feet of enclosed storage space.

3.5.2.1 Compartment doors. Storage compartments will have clear anodized aluminum, counterbalanced, non-locking, roll-up or single hinged doors as determined by the manufacturer. Door latch handles on roll-up doors will be full-width bar type. Door straps will be provided to assist in closing the compartment doors when the rolled up or hinged door height exceeds six feet above the ground.

3.5.2.2 Scuffplates. Replaceable scuffplates will be provided at each compartment threshold to prevent body damage from sliding equipment in and out of the compartments. The

scuffplates will be securely attached to the compartment threshold but will be easily replaceable in the event of damage.

3.5.2.3 Drip rails. Drip rails will be provided over each compartment door.

3.5.2.4 Shelves. An adjustable and removable compartment shelf will be provided for every 18 inches of each vertical storage compartment door opening. Shelving adjustments will require no more than common hand tools, and will not require disassembly of fasteners. Shelves will support a minimum of 200 pounds without permanent deformation. Each shelf will be accessible to crew members standing on the ground or using a pull out and tip-down configuration. Each shelf will have drain holes located so as to allow for drainage of any water from the stowed equipment.

3.5.2.5 Drainage mats. Each compartment floor and shelf will be covered with a removable black mat designed to allow for drainage of any water from the stowed equipment.

3.5.3 SCBA storage tubes. A single compartment or tubes for storage of four SCBA bottles will be provided. If tubes are provided, two will be installed on each side of the vehicle. The tubes will be of sufficient size to accommodate the procuring agencies SCBA cylinders.

3.5.4 Ladder, handrails, and walkways. Ladder, stepping, standing, and walking surfaces will be in accordance with NFPA 414. Handrails will be provided in accordance with NFPA 414. The lowermost step(s) or ladder rungs will be no more than 22 inches (56 cm) above level ground when the vehicle is fully loaded. The lowermost steps may extend below the angle of approach or departure or ground clearance limits if they are designed to swing clear. The tread of the bottom steps must be at least 8 inches (20 cm) in width and succeeding steps at least 16 inches (40 cm) in width. The full width of all steps must have at least 6 inches (15 cm) of unobstructed toe room or depth when measured from, and perpendicular to, the front edge of the weight-bearing surface of the step.

3.5.5 Ancillary equipment. Ancillary equipment listed in NFPA 414 A.4.2.1 (1)-(17) is not covered by this Procurement Specification in accordance with AC 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles. Ancillary equipment is funded separately by other sources.

NOTE: Equipment funding will be obtained as a separate contract under the provisions of AC 150/5210-14, Aircraft Rescue and Fire Fighting Equipment, Tools, and Clothing.

3.6 Agent system.

3.6.1 Agent (fire) pump. The vehicle will be equipped with a centrifugal pump capable of providing the performance specified herein as prescribed by NFPA 414.

3.6.1.1 Agent system piping. All piping, couplings, and valves and associated components that come into contact with the agent will be in accordance with NFPA 414.

3.6.1.2 Tank to pump connection. A check valve and shutoff valve will be provided in each tank to pump line.

3.6.1.3 Piping, couplings, and valves. All agent system piping will conform to NFPA 414 criteria.

3.6.1.4 Overheat protection. The agent system will be equipped with an overheat protection system in accordance with NFPA 414. Overheat protection is not required on vehicles utilizing a pre-mixed pressurized foam system.

3.6.1.5 Pressure relief valves. The agent system will be equipped with pressure relief valves in accordance with NFPA 414.

3.6.1.6 Drains. The agent system will be equipped with a drainage system in accordance with NFPA 414.

3.6.2 Water tank. The vehicle will have a water tank with a manufacturer certified minimum capacity of at least 3000 gallons.

3.6.2.1 Water tank construction. The water tank will be constructed of passivated stainless steel, polypropylene, or Glass Reinforced Polyester (GRP) construction. All materials used will be capable of storing water, foam concentrate, and water/AFFF solutions.

3.6.2.2 Water tank overhead fill cover and drain. The water tank will be equipped with a 20 inch fill tower. The tower will be designed to allow for video inspection of the water tank interior. The water tank will incorporate a drainage system in accordance with NFPA 414.

3.6.2.3 Water tank overflow system and venting. The water tank will incorporate a venting system to relieve pressure on the tank during fill and discharge operations at maximum flow rates. It will have an overflow system to relieve excess fluid in the event of tank overflow. Drainage from the vent and overflow system will not flow over body panels or other vehicle components and will not be in the track of any of the tires. Tank vent hoses will be of the non-collapsible type.

3.6.2.4 Water tank top fill opening. A top fill opening of not less than 8 inches internal diameter with a readily removable ¼-inch mesh strainer will be provided. The fill opening may be incorporated as part of the manhole cover, and will be sized to accommodate a 2½-inch fill hose.

3.6.2.5 Water tank fill connections. The water tank will incorporate National Hose thread connections and will be in accordance with NFPA 414. If the vehicle is fitted with the "structural fire fighting capability option," the additional requirements listed in paragraph 3.6.8 must be incorporated.

3.6.3 Foam system. (NOTE: *The requirements of section 3.6.3 do not apply to pre-mixed pressurized foam systems.*)

3.6.3.1 Foam concentrate tank. The foam concentrate tank(s) will have a manufacturer certified working capacity sufficient for two tanks of water at the maximum tolerance specified in NFPA 412, Standard for Evaluating Aircraft Rescue and Fire-Fighting Foam Equipment for 3 to 6 percent foam concentrate (i.e., 7.0-percent).

3.6.3.1.1 Foam tank construction. The foam tank will be constructed of passivated stainless steel, polypropylene, or GRP construction. All materials used will be capable of storing foam concentrate.

3.6.3.1.2 Foam tank drain. The foam tank will incorporate a drain and drain valve. The valve will be on the left side of the vehicle and controlled by a crew member standing on the ground. The drain line will have a minimum 1½-inch I.D. The foam tank drain outlet will be located so that the contents of the tank can be drained into 5-gallon cans and 55-gallon drums.

3.6.3.1.3 Foam tank top fill trough. The foam tank will incorporate a top fill trough mounted in the top of the tank readily accessible to at least two crew members on top of the vehicle. The top fill trough will incorporate a cover, latch, and sealed so as to prevent spillage under any operating condition. The top fill trough will be designed to allow two standard 5-gallon foam concentrate containers to be emptied simultaneously. The top fill trough neck will extend sufficiently close to the bottom of the tank to reduce foaming to a minimum during the fill operation. The top fill trough will incorporate readily removable, rigidly constructed 10 mesh stainless steel, brass or polyethylene strainers. All components in and around the top fill trough will be constructed of materials that resist all forms of deterioration that could be caused by the foam concentrate or water.

3.6.3.2 Foam tank fill connections. The foam tank will incorporate a 1.5-inch National Hose thread female hose connection on the left side of the vehicle to permit filling by an external transfer hose at flow rates up to 25-gpm. The connections will be provided with chained-on long handled plugs or rocker lug plugs. The top of the connections will be no higher than 48 inches above the ground and readily accessible. The fill lines will incorporate check valves and readily removable, rigidly constructed ¼-inch mesh strainers. All components in the foam tank fill system will be constructed of materials that resist all forms of deterioration that could be caused by the foam concentrate or water.

3.6.3.2.1 Foam tank vent and overflow system. The foam tank will incorporate a vent system to relieve pressure on the tank during fill and discharge operations at maximum flow rates and an overflow system to relieve excess liquid in the event of tank overfill. Drainage from the vent and overflow system will not flow over body panels or other vehicle components and will not be in front of or behind any of the tires. Tank vent hoses will be of the non-collapsible type.

3.6.3.3 Foam transfer pump. A foam transfer pump will be provided and mounted in a compartment on the vehicle. The pump will be capable of transferring and drawing foam liquid concentrate at adjustable flow rates up to 25-gpm directly through the pump and loading connections (see 3.6.3.2). All materials and components that come in contact with the foam will be compatible with the foam concentrate. The pump and its plumbing will have provisions for flushing with water from the water tank. A suitable length of hose with appropriate connections will be provided for filling the foam tank from an external foam storage container.

3.6.3.4 Foam flushing system. The foam concentrate system will be designed in accordance with NFPA 414 so that the system can be readily flushed with clear water.

3.6.3.5 Foam concentrate piping. All metallic surfaces of the piping and associated components that come into contact with the foam concentrate will be of brass, bronze, or passivated stainless steel. The foam concentrate piping will be in accordance with NFPA 414.

3.6.4 Foam proportioning system. The vehicle will have a foam proportioning system for Aqueous Film-Forming Foam (AFFF) (whether 3- or 6-percent foam concentrate) in accordance with NFPA 414. If a fixed orifice plate system is used, a plate will be provided for each percentage foam concentrate; the additional plate will be securely mounted in a protected location on the vehicle. A fire vehicle mechanic will be able to interchange the plates using common hand tools.

3.6.5 Primary vehicle turret. The vehicle will be equipped with a standard roof-mounted turret, high reach extendable turret, and/or high flow bumper mounted turret to serve as the primary source of agent delivery, as specified below:

3.6.5.1. The vehicle will be equipped with a high reach extendable turret (capable of penetrating the second level of the New Large Aircraft (NLA) class of aircraft, in accordance with paragraph 3.6.5.2. The NLA class aircraft are equivalent to the 'Airplane Design Group VI' category, as specified in AC 150/5300-13, Airport Design.

NOTE: AC 150-5220-10 allows one vehicle equipped with a high reach extendable turret for an Index B-E airport at each airport station.

3.6.5.2 High Reach Extendable Turret (capable of penetrating all aircraft except the second level of an NLA). The high reach extendable turret (HRET) must be in accordance with NFPA 414 and will have the vertical and horizontal reach necessary to service the highest placed engine of the aircraft being serviced. It will have a non-air-aspirating, constant flow, variable stream nozzle with dual flow rates for foam or water rated as specified in NFPA 414. The discharge pattern will be infinitely variable from straight stream to fully dispersed. The type of nozzle or turret drain will be per the manufacturer's recommendation. The ET will be controlled by one or two joysticks, each with a pistol grip handle, positioned for use by the driver and the crew member seated to the right of the driver (the turret operator). The cab design will provide clear visibility of the turret to both the driver and the turret operator with the turret in any position.

3.6.5.2.1 Video camera and monitor. The HRET will be equipped with a remote video camera and a cab mounted monitor. The system will be a complete video system consisting of a single color camera equipped with auto-focus and a cab controlled zoom. The camera/lens assembly will be protected from the heat of the fire and from the same climatic extremes as the truck. A color video monitor with a minimum dimension of 10 inches (measured diagonally) will be positioned in the cab within view of both the driver's and the turret operator's seated positions. One monitor may be provided for both the FLIR (see 3.4.5) and the camera with a switch to change between the FLIR and the camera.

3.6.5.2.2 Aircraft skin penetrator. The HRET will be equipped with an aircraft skin penetrator and agent application tool. The skin penetrator will be a minimum of 20 inches long, installed at the tip of the HRET, and connected to the water/AFFF agent discharge line. Agent application through the skin penetrator will be controlled from the cab. NOTE: If a high reach extendable turret is specified by the purchaser, a skin penetrating nozzle must be provided. The penetrating nozzle must be movable to allow for proper alignment of the penetrator to the aircraft fuselage for piercing operations. It must be capable of the minimum water/flow rate and pattern requirements of NFPA 414, Tables 4.1.1(c) and 4.1.1(d).

3.6.6 Bumper turret. The vehicle will be equipped with a joystick controlled, constant flow, non-air-aspirating, variable stream type:

low angle high volume dual rate (minimum 600/1200 GPM) bumper turret.

The bumper turret will be capable of discharging at a minimum flow rate of foam or water as specified by the user, with a pattern infinitely variable from straight stream to fully dispersed. The bumper turret will be capable of automatic oscillation, with the range of oscillation adjustable up to 90° each side of center (left and right) with vertical travel capabilities of +45°/-20° meeting section 4.20.2 in NFPA 414.

3.6.7 Preconnected handline(s). Two 200 foot, 1¾-inch pre-connected woven jacket handline(s), with a 1½-inch control valve and a pistol grip nozzle, will be located on (or accessible from) each side of the vehicle. A safety system will be provided to prevent charging of the hose until the hose has been fully deployed. The handline(s) and nozzle(s) will be in accordance with NFPA 414, and will allow for a minimum of 95 gpm at 100 psi nozzle pressure. A control for charging each handline will be provided for operation by both the driver and the turret operator.

3.6.7.1 In addition, the vehicle will be equipped with the following handline: 150 feet of 1-inch dry chemical hose on a reel.

3.6.8. Structural fire fighting capability. The vehicle will be equipped with an agent system structural control panel, on the left side of the vehicle, operable while standing on the ground. Structural panel activation will be interlocked to operate only with the vehicle parking brakes set and the transmission in neutral position. Controls and instruments will be grouped by function. The control panel will be hinged or accessible from the rear for maintenance. Instruments will be lighted for night operation.

3.6.8.1 The structural panel will include, as a minimum, the following:

- a. Panel activation switch, including the panel lights.
- b. Engine tachometer.
- c. Engine oil pressure gauge with low pressure warning light.
- d. Engine coolant temperature gauge with high temperature warning light.
- e. A liquid filled gauge, or digital indicator for pump suction, -30 inches Hg vacuum to 600 psi.
- f. A liquid filled gauge, or digital indicator for pump pressure, 0 to 600 psi.
- g. An adjustable pump pressure using either an electronic pressure governor or manual control with a relief valve will be provided.
- h. Foam or water selection.
- i. Water and foam tank liquid level indicators, located adjacent to the water and foam tank fills.

3.6.8.2 The structural fire fighting capability will also require installation of the following items:

- a. A priming pump and control (for drafting using the large intake connection).
- b. Water tank isolation valve.
- c. Discharge connections. Two 2½-inch discharge connections with male National Hose threads will be provided. One 2½-inch discharge will be provided on each side of the vehicle. Each connection will be equipped with a cap, a quarter-turn control valve, a bleeder valve, and a pressure gauge. Each connection will be rated at 250-gpm minimum.
- d. Intake connections. The vehicle will be equipped with one valved 4½-inch intake connection on the left side. The vehicle will be equipped with one valved 2½-inch intake connection on the left side adjacent to the 4½-inch intake connection with both having either a 30° or 45° turn-down fitting. The 4½-inch intake connection will have male National Hose threads, a quarter-turn control valve, a bleeder valve, a strainer, and a cap. The 2½-inch intake connection will have rocker lug female National Hose threads, a quarter-turn control valve, a bleeder valve, a strainer, and a plug. The vehicle will be capable of filling its water tank by pumping from a draft, a hydrant, or a nurse truck through either of the intake connections without the use of a hose from a discharge connection to a tank fill connection.

3.6.9 Primary turret discharge nozzle. The vehicle will be equipped with a combination dry chemical/ AFFF nozzle of the entrainment type on the primary turret mounted on the front bumper.

3.7 Dry chemical agent system. The vehicle will be equipped with a 500 lb minimum capacity sodium based dry chemical agent system. The propellant gas cylinder will be replaceable within fifteen minutes by two crew members standing on the ground and be equipped with a cylinder replacement hoisting system. The propellant gas cylinder will be secured to withstand off-road operations. A pressure indicator will be visible to any person opening the tank fill cap. Blow-down piping will be directed beneath the vehicle. The dry chemical agent tank will include lifting rings and will have a nameplate indicating, as a minimum, the following:

- a. Extinguishing agent.
- b. Capacity.
- c. Weight full.
- d. Weight empty.
- e. Operating pressure.
- f. Hydrostatic test date.
- g. Type of agent required for re-servicing.

3.7.1 Not applicable.

3.7.2 Dry chemical hose reel. A hose reel, equipped with at least 100 feet of dry chemical hose, will be mounted in a compartment. Handline agent and purge controls will be mounted in or adjacent to the compartment. All electrical components will be sealed against entry of water. The hose reel will have both electric and manual rewind provisions. The manual rewind handle will be bracket mounted and stored in the compartment. A quick acting control will be provided to activate the handline from the cab of the vehicle.

3.8 Not applicable.

3.9 Electrical systems and warning devices. The vehicle will have a 12-volt or 24-volt electrical and starting system in accordance with NFPA 414.

3.9.1 Alternator. An appropriate charging system, in accordance with NFPA 414, will be provided. The minimum continuous electrical load will include operation of the air conditioning system.

3.9.2 Batteries. Batteries will be of the maintenance-free type; addition of water will not be required during normal service life. The battery cover and vent system will be designed to prevent electrolyte loss during service and to keep the top of the battery free from electrolyte.

3.9.2.1 Battery compartment. The batteries will be enclosed in a weatherproof enclosure, cover, or compartment and be readily accessible.

3.9.3 Battery charger or conditioner. The vehicle will have a DC taper type battery charger or an automatic battery conditioner, or voltage monitoring system, providing a minimum 12 amp output. The charger/conditioner will be permanently mounted on the vehicle in a properly ventilated, accessible location. The charger/conditioner will be powered from the electrical shoreline receptacle (see 3.10.1). A charging indicator will be installed next to the receptacle. When a battery conditioner is provided, the conditioner will monitor the battery state of charge and, as necessary, automatically charge or maintain the batteries without gassing, depleting fluid level, overheating, or overcharging. A slave receptacle will be provided at the rear or on either side of the vehicle cab. Battery jump studs may be installed on the exterior of the battery box in lieu of a slave receptacle.

3.9.4 Electromagnetic interference. The vehicle electrical system will be in accordance with SAE J551-2 for electromagnetic interference.

3.9.5 Work lighting.

3.9.5.1 Cab interior lights. Cab interior light levels will be sufficient for reading maps or manuals. At least one red and one white cab interior dome light will be provided.

3.9.5.2 Compartment lights. White lighting sufficient to provide an average minimum illumination of 1.0 footcandle will be provided in each compartment greater than 4.0 cubic feet and having an opening greater than 144 square inches. Where a shelf is provided, this illumination will be provided both above and below the shelf. All compartments will be provided with weatherproof lights that are switched to automatically illuminate when compartment doors are opened and the vehicle master switch is in the 'on' position. Light switches will be of the magnetic (non-mechanical) type.

3.9.5.3 Ladder, step, walkway, and area lights. Non-glare white or amber lighting will be provided at ladders and access steps where personnel work or climb during night operations. In addition, ground lighting will be provided. Ground lights will be activated when the parking brake is set in accordance with AC 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles. These area lights will be controlled with three-way switches on the cab instrument panel and near the light sources. The switch located in the cab will be a

master switch and must be turned on before auxiliary switches near the light sources are operational.

3.9.5.4 Spot/Floodlights. Two spot/floodlights will be attached at the end of the primary turret or at the end of the HRET assembly. The lights will illuminate the area covered by the turret. Both lights will be controlled from switches in the cab. LED lights will be used.

3.9.5.5 Flood Lights. Two fixed floodlights will be provided. One light will be mounted on the left and right sides of the vehicle. 250W LED lights will be used. Both lights will be controlled from switches in the cab and will be powered by the auxiliary generator.

3.9.5.6 Scene Lights. A total of six high mounted floodlights will be provided to illuminate the work areas around the vehicle. Two lights will be mounted on the front and two will be mounted on each side of the vehicle. The lights will be powered by the vehicle alternator driven system or auxiliary generator, and the lights in the front will be controlled from switches in the cab. LED lights will be used.

3.9.6 Audible warning devices.

3.9.6.1 Siren. The vehicle will be equipped with an electronic siren system. The amplifier unit will include volume control and selection of "Radio," "PA," "Manual," "Yelp," "Wail," and "Hi-Lo" (European) modes, and a magnetic noise canceling microphone. The amplifier, microphone, and controls will be within reach of the driver and the turret operator. Siren activating foot switches will be located in front of the driver and the turret operator. The siren speaker will be rated at 100 watts minimum and will be located in a guarded position as low and as far forward on the vehicle as practical.

3.9.6.2 Horn. Dual forward facing air horns will be installed in protected locations near the front of the vehicle. Air horn activating foot switches will be located in front of the driver and the turret operator.

3.9.7 Emergency warning lights. All emergency warning lights must meet the requirements of AC 150/5210-5. Where applicable, LED lights will be used as the primary light type. Lighting units will be installed on the top front, sides, and rear of the vehicle to provide 360° visibility. A switch will be provided on the instrument panel to control all of the top, side, front and rear emergency warning lights. A switch will also be provided on the instrument panel to disable all lower emergency warning lights when desired. All lighting systems will meet NFPA 414 emergency lighting criteria.

3.9.7.1 Emergency warning light color. All emergency warning lights will meet the requirements of AC 150/5210-5.

3.9.7.2 Headlight flashing system. A high beam, alternating/flashing, headlight system will be provided. The headlight flasher will be separately switched from the warning light panel.

3.9.8 Radio circuit. The vehicle will have three separate 30 amp circuits with breakers and connections provided in a space adjacent to the driver and turret operator for installation of radios and other communications equipment after the vehicle has been delivered. To facilitate the installation of the communications equipment the manufacturer will provide three antennas pre-installed on top of the cab. *Radios are an airport responsibility and not part of this specification.*

3.9.9 Power receptacles.

3.9.9.1 Primary power receptacles. The vehicle will have two duplex 15-amp 110-volt power receptacles, one installed adjacent to the cab door on each side of the vehicle. Each duplex receptacle will include one straight blade and one twist-lock connection. These outlets will be powered by the generator.

3.9.9.2 Auxiliary power receptacles. The vehicle will have 2-12-volt auxiliary power receptacles mounted adjacent to the driver and crew member positions, preferably in the instrument panel.

3.9.9.3 Cable reel. The vehicle will be equipped with an electrical cable reel, located within a compartment. The reel will be equipped with 200 feet of 20 amp, 600 volt, 90°C insulated electrical cable. The electrical cable will be equipped with a rubber ball stop to prevent cable pull through during rewinding operations. A four-way roller guide will be provided on the cable reel to prevent chafing of cable insulation. The cable reel will have an electric rewind motor with provisions for manual rewind in the event of motor failure; the manual rewind handle will be securely stored near the cable reel. A portable weatherproof duplex outlet box, with built-in circuit breakers and twist-lock receptacles, will be provided for on the cable end. The cable reel will be powered by the auxiliary generator.

3.9.10 Auxiliary generator. A minimum 10 kilowatt (kW) (continuous rating), 120/240-volt, 60 hertz, diesel, hydraulic, or split shaft Power Takeoff (PTO)-driven generator will be provided.

3.10 Line voltage electrical system.

3.10.1 Electrical shoreline connection. The battery charger/conditioner will be powered from a covered, polarized, insulated, labeled, recessed (flush mounted), male, 110 volt AC auto-eject receptacle. The connection will be located on the exterior of the vehicle at the rear or on either side of the cab. A weatherproof charge meter will be installed next to the receptacle. A 15 amp rated, 110-120-volt, AC straight blade (non twist-lock) connector will be provided.

3.11 Air systems.

3.11.1 Air hose reel. An air hose reel will be provided in an enclosed compartment on the vehicle. The hose reel will be equipped with 200 feet of 3/8-inch I.D. hoseline. A 3/8 inch National Pipe Taper (NPT) fitting and female style quick disconnect will be connected to the end of the hoseline. A four-way roller guide will be provided for the hose reel to prevent hose chafing and kinking. The hoseline will be equipped with a rubber ball stop to prevent hose pull through on roller guides during rewinding operations. The hose reel will have an electric rewind motor and provisions for manual rewind in the event of motor failure; the manual rewind handle will be securely stored near the hose reel. A pressure protected air supply from the chassis air system will be connected to the hose reel. The air supply lines will be routed with minimum bends and located or guarded from damage from the carried equipment.

3.12 Quality of Workmanship. The vehicle, including all parts and accessories, will be fabricated in a thoroughly workmanlike manner. Particular attention will be given to freedom from blemishes, burrs, defects, and sharp edges; accuracy of dimensions, radii of fillets, and marking of parts and assemblies; thoroughness of welding, brazing, soldering, riveting, and painting; alignment of parts; tightness of fasteners; et cetera. The vehicle will be thoroughly cleaned of all foreign matter.

4. REGULATORY REQUIREMENTS.

4.1 Recoverable Materials. The contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with Title 48: Federal Acquisition Regulations System, Part 2823—Environment, Conservation, Occupational Safety, and Drug-free Workplace, Subpart 2823.4 Use of Recovered Material, 403 Policy and 404 Procedures.

4.2 Green Procurement Program. Green Procurement Program (GPP) is a mandatory federal acquisition program that focuses on the purchase and use of environmentally preferable products and services. GPP requirements apply to all acquisitions using appropriated funds, including services and new requirements. FAR 23.404(b) applies and states the GPP requires 100% of EPA designated product purchase that are included in the Comprehensive Procurement Guidelines list that contains recovered materials, unless the item cannot be acquired:

- a. competitively within a reasonable timeframe;
- b. meet appropriate performance standards, or
- c. at a reasonable price.

The prime contractor is responsible for ensuring that all subcontractors comply with this requirement. Information on the GPP can be found at:

http://www.dot.gov/ost/m60/DOT_policy_letters/apl8_04.pdf or FAR 23.404(b):
http://www.acquisition.gov/far/current/html/Subpart%2023_4.html.

5. PRODUCT CONFORMANCE PROVISIONS.

5.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

- a. Performance inspection (see 5.2).
- b. Conformance inspection (see 5.3).

5.2 Performance inspection. The vehicle will be subjected to the examinations and tests described in 5.6.3.1 through 5.6.3.5 (if applicable). The contractor will provide or arrange for all test equipment, personnel, schedule, and facilities.

5.3 Conformance inspection. The vehicle will be subjected to the examinations and tests described in 5.6.3.1 through 5.6.3.5 (if applicable). The contractor will provide or arrange for all test equipment, personnel, and facilities.

5.4 Product conformance. The products provided will meet the performance characteristics of this PS, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The purchaser reserves the right to require proof of such conformance.

5.5 Technical proposal. The offeror/contractor will provide an itemized technical proposal that describes how the proposed model complies with each characteristic of this PS; a paragraph by paragraph response to the characteristics section of this PS will be provided. The offeror/contractor will provide two copies of their commercial descriptive catalogs with their offer as supporting reference to the itemized technical proposal. The offeror/contractor will identify all modifications made to their commercial model in order to comply with the requirements herein. The vehicle furnished will comply with the "commercial item" definition of FAR 2.101 as of the date of award. The purchaser reserves the right to require the offeror/contractor to prove that their product complies with the referenced commerciality requirements and each conformance/performance characteristics of this PS.

5.6 Inspection requirements.

5.6.1 General inspection requirements. Apparatus used in conjunction with the inspections specified herein will be laboratory precision type, calibrated at proper intervals to ensure laboratory accuracy.

5.6.2 Test rejection criteria. Throughout all tests specified herein, the vehicle will be closely observed for the following conditions, which will be cause for rejection:

- a. Failure to conform to design or performance requirements specified herein or in the contractor's technical proposal.
- b. Any spillage or leakage of any liquid, including fuel, coolant, lubricant, or hydraulic fluid, under any condition, except as allowed herein.
- c. Structural failure of any component, including permanent deformation, or evidence of impending failure.
- d. Evidence of excessive wear.
- e. Interference between the vehicle components or between the vehicle, the ground, and all required obstacles, with the exception of normal contact by the tires.
- f. Misalignment of components.

- g. Evidence of undesirable roadability characteristics, including instability in handling during cornering, braking, and while traversing all required terrain.
- h. Conditions that present a safety hazard to personnel during operation, servicing, or maintenance.
- i. Overheating of the engine, transmission, or any other vehicle component.
- j. Evidence of corrosion.
- k. Failure of the fire fighting system and sub-systems.

5.6.3 Detailed inspection requirements.

5.6.3.1 Examination of product. All component manufacturers' certifications, as well as the prototype and production/operational vehicle testing outlined in Table 1, will be examined to verify compliance with the requirements herein. Attention will be given to materials, workmanship, dimensions, surface finishes, protective coatings and sealants and their application, welding, fastening, and markings. Proper operation of vehicle functions will be verified as defined by NFPA 414, Acceptance Criteria chapter. A copy of the vehicle manufacturer's certifications will be provided with each vehicle in accordance with NFPA 414. The airport may accept a manufacturer or third party certification for any/all prototype and production/operational vehicle testing performed prior to delivery which proves that the vehicle meets the performance parameters of NFPA 414.

Table 1. Vehicle Test Data

<i>NFPA 414 paragraph</i>	<i>Test</i>
Production Vehicle Operational Tests (NFPA 414 - Section 6.4)	
(6.4.1)	Vehicle Testing, Side Slope
(6.4.2)	Weight / Weight Distribution
(6.4.3)	Acceleration. NOTE: <i>With the modification that the instrumentation must be a GPS-based electronic data collection system.</i>
(6.4.4)	Top Speed
(6.4.5)	Brake Operational Test
(6.4.6)	Air System / Air Compressor Test
(6.4.7)	Agent Discharge Pumping Test
(6.4.8)	Dual Pumping System Test (As Applicable)
(6.4.9)	Pump and Maneuver Test
(6.4.10)	Hydrostatic Pressure Test
(6.4.11)	Foam Concentration Test
(6.4.12)	Primary Turret Flow Rate Test
(6.4.13)	Piercing/Penetration Nozzle Testing (As Applicable)
Prototype Vehicle Tests (NFPA 414 – Section 6.3)	
(6.3.1)	Rated Water and Foam Tank Capacity Test
(6.3.2)	Cornering Stability. NOTE: <i>With the modification that the evasive maneuver / double-lane change test must be conducted at 35 mph (56 kph).</i>
(6.3.3)	Vehicle Dimensions

<i>NFPA 414 paragraph</i>	<i>Test</i>
(6.3.4)	Driver Vision Measurement
(6.3.5)	Pump and Roll on a 40 Percent Grade
(6.3.6)	Electrical Charging System
(6.3.7)	Radio Suppression
(6.3.8)	Gradability Test
(6.3.9)	Body and Chassis Flexibility Test
(6.3.10)	Service/Emergency Brake Test
(6.3.11)	Service/Emergency Brake Grade Holding Test
(6.3.12)	Steering Control Test
(6.3.13)	Vehicle Clearance Circle Test
(6.3.14)	Agent Pump(s)/Tank Vent Discharge Test
(6.3.15)	Water Tank Fill and Overflow Test
(6.3.16)	Flushing System Test
(6.3.17)	Primary Turret Flow Rate Test
(6.3.18)	Primary Turret Pattern Test
(6.3.19)	Primary Turret Control Force Measurement
(6.3.20)	Primary Turret Articulation Test
(6.3.21)	Handline Nozzle Flow Rate Test
(6.3.22)	Handline Nozzle Pattern Test
(6.3.23)	Ground Sweep/Bumper Turret Flow Rate Test
(6.3.24)	Ground Sweep/Bumper Turret Pattern Control Test
(6.3.25)	Undertruck Nozzle Test
(6.3.26)	Foam Concentration/Foam Quality Test
(6.3.27)	Warning Siren Test
(6.3.28)	Propellant Gas
(6.3.29)	Pressure Regulation
(6.3.30)	AFFF Premix Piping and Valves
(6.3.31)	Pressurized Agent Purging and Venting
(6.3.32)	Complementary Agent Handline Flow Rate and Range
(6.3.33)	Dry Chemical Turret Flow Rate and Range
(6.3.34)	Cab Interior Noise Test

6. PACKAGING.

6.1 Preservation, packing, and marking will be as specified in the Procurement Specification, contract or delivery order.

6.2 The vehicle must be delivered with full operational quantities of lubricants, brake and hydraulic fluids, and cooling system fluid all of which must be suitable for use in the temperature range expected at the airport.

6.3 The vehicle must be delivered with one complete load of firefighting agents and propellants. One complete load is defined as all of the agents and propellants necessary for the vehicle to be fully operational. One load would include, at a minimum: one fill of a foam tank;

one fill of a dry chemical tank (if applicable); one fill of a halogenated tank (if applicable); one spare nitrogen cylinder for a dry chemical system (if applicable); and one spare argon cylinder for a halogenated system (if applicable). Agents and propellants for required testing or training are not included. For the initial training period, water should be used in place of other extinguishing agents. The manufacturer may pre-ship agents and propellants to a receiving airport to reduce overall procurement costs.

6.4. The vehicle manufacturer must provide initial adjustments to the vehicle for operational readiness and mount any ancillary appliances purchased through the vehicle manufacturer as part of the vehicle.

7. TRAINING.

7.1 Upon delivery of the vehicle to the airport, the manufacturer must, at no additional cost, provide the services of a qualified technician for five consecutive days (or up to eight days for an high reach extendable turret) for training. This is considered sufficient time for the purchaser to adjust shift work schedules to get maximum employee attendance to training sessions at some point during the training period. During this time sufficient repetitive learning opportunities must be provided by the manufacturer to allow various shifts to complete the training requirements.

7.2 The technician must provide thorough instruction in the use, operation, maintenance and testing of the vehicle. This setup must include operator training for the primary operators, which will give them sufficient knowledge to train other personnel in the functional use of all fire fighting and vehicle operating systems. Prior to leaving the vehicle, the technician should review the maintenance instructions with the purchaser's personnel to acquaint them with maintenance procedures as well as how to obtain support service for the vehicle.

7.3 Training must include written operating instructions, electronic training aids (videos/power point), or other graphics that depict the step-by-step operation of the vehicle. Written instructions must include materials that can be used to train subsequent new operators.

8. REFERENCED DOCUMENTS.

8.1 Source of documents.

8.1.1 The CFR may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington DC 20402.

Title 14, Code of Federal Regulations (CFR), Part 139, Certification of Airports (14 CFR Part 139)

Section 139.315 Aircraft Rescue and Firefighting: Index Determination.

Section 139.317 Aircraft Rescue and Firefighting: Equipment and Agents.

Section 139.319 Aircraft Rescue and Firefighting: Operational Requirements.

Title 49; Code of Federal Regulations (CFR), Part 393: Parts and Accessories Necessary for Safe Operation: Subpart C—Brakes.

Title 49; Code of Federal Regulations (CFR), Part 571, Motor Carrier Vehicle Safety Standards, Part 209, Standard No. 209; Seat Belt Assemblies.

8.1.2 SAE documents may be obtained from SAE, Inc., 400 Commonwealth Drive, Warrendale PA 15096.

8.1.3 National Fire Protection Association (NFPA): NFPA documents may be obtained from NFPA, Batterymarch Park, Quincy MA 02269-9101.

NFPA 412, Standard for Evaluating Aircraft Rescue and Fire-Fighting Foam Equipment (2009 Edition)

NFPA 414, Standard for Aircraft Rescue and Fire Fighting Vehicles (2007 Edition)

NFPA 1901, Standard for Automotive Fire Apparatus (2009 Edition)

8.1.4 Federal Aviation Administration (FAA): FAA ACs may be obtained from the FAA website: http://www.faa.gov/regulations_policies/advisory_circulars/

AC 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles

AC 150/5210-5, Painting, Marking, and Lighting of Vehicles Used on an Airport

FAA Orders, Specifications, and Drawings may be obtained from: Federal Aviation Administration, ATO-W CM-NAS Documentation, Control Center, 800 Independence Avenue, SW, Washington, DC 20591. Telephone: (202) 548-5256, FAX: (202) 548-5501 and website: http://www.faa.gov/about/office_org/headquarters_offices/ato/service_units/techops/atc_facilities/cm/cm_documentation/



Print Class 5 Specification

Exhibit B – Federal Provisions

NOTICE OF REQUIREMENT FOR AFFIRMATIVE ACTION TO ENSURE EQUAL EMPLOYMENT OPPORTUNITY

1. The Offeror's or Bidder's attention is called to the "Equal Opportunity Clause" and the "Standard Federal Equal Employment Opportunity Construction Contract Specifications" set forth herein.
2. The goals and timetables for minority and female participation, expressed in percentage terms for the Contractor's aggregate workforce in each trade on all construction work in the covered area, are as follows:

Timetables

Goals for minority participation for each trade:

Goals for female participation in each trade: 6.9%

These goals are applicable to all of the Contractor's construction work (whether or not it is Federal or federally assisted) performed in the covered area. If the Contractor performs construction work in a geographical area located outside of the covered area, it shall apply the goals established for such geographical area where the work is actually performed. With regard to this second area, the Contractor also is subject to the goals for both its federally involved and nonfederally involved construction.

The Contractor's compliance with the Executive Order and the regulations in 41 CFR Part 60-4 shall be based on its implementation of the Equal Opportunity Clause, specific affirmative action obligations required by the specifications set forth in 41 CFR 60-4.3(a) and its efforts to meet the goals. The hours of minority and female employment and training must be substantially uniform throughout the length of the contract, and in each trade, and the Contractor shall make a good faith effort to employ minorities and women evenly on each of its projects. The transfer of minority or female employees or trainees from Contractor to Contractor or from project to project for the sole purpose of meeting the Contractor's goals shall be a violation of the contract, the Executive Order and the regulations in 41 CFR Part 60-4. Compliance with the goals will be measured against the total work hours performed.

3. The Contractor shall provide written notification to the Director of the Office of Federal Contract Compliance Programs (OFCCP) within 10 working days of award of any construction subcontract in excess of \$10,000 at any tier for construction work under the contract resulting from this solicitation. The notification shall list the name, address, and telephone number of the subcontractor; employer identification number of the subcontractor; estimated dollar amount of the subcontract; estimated starting and completion dates of the subcontract; and the geographical area in which the subcontract is to be performed.

4. As used in this notice and in the contract resulting from this solicitation, the "covered area" is Grand Rapids, Kent County, Michigan.

FAA BUY AMERICAN PREFERENCE

The Contractor certifies that its bid/offer is in compliance with 49 USC § 50101, BABA and other related Made in America Laws, 1 U.S. statutes, guidance, and FAA policies, which provide that Federal funds may not be obligated unless all iron, steel and manufactured goods used in AIP funded projects are produced in the United States, unless the Federal Aviation Administration has issued a waiver for the product; the product is listed as an Excepted Article, Material Or Supply in Federal Acquisition Regulation subpart 25.108; or is included in the FAA Nationwide Buy American Waivers Issued list.

The bidder or offeror must complete and submit the certification of compliance with FAA's Buy American Preference, BABA and Made in America laws included herein with their bid or offer. The Airport Sponsor/Owner will reject as nonresponsive any bid or offer that does not include a completed certification of compliance with FAA's Buy American Preference and BABA.

The bidder or offeror certifies that all constructions materials, defined to mean an article, material, or supply other than an item of primarily iron or steel; a manufactured product; cement and cementitious materials; aggregates such as stone, sand, or gravel; or aggregate binding agents or additives that are or consist primarily of: non-ferrous metals; plastic and polymer-based products (including polyvinylchloride, composite building materials, and polymers used in fiber optic cables); glass (including optic glass); lumber; or drywall used in the project are manufactured in the U.S.

Certification of Compliance with FAA Buy American Preference – Equipment/Building Projects

As a matter of bid responsiveness, the bidder or offeror must complete, sign, date, and submit this certification statement with their proposal. The bidder or offeror must indicate how they intend to comply with 49 USC § 50101, and other Made in America Laws, U.S. statutes, guidance, and FAA policies by selecting one on the following certification statements. These statements are mutually exclusive. Bidder must select one or the other (not both) by inserting a checkmark (✓) or the letter "X".

- ☐ Bidder or offeror hereby certifies that it will comply with 49 USC § 50101, BABA and other related U.S. statutes, guidance, and policies of the FAA by:
- a) Only installing steel and manufactured products produced in the United States;
 - b) Only installing construction materials defined as: an article, material, or supply – other than an item of primarily iron or steel; a manufactured product; cement and cementitious materials; aggregates such as stone, sand, or gravel; or aggregate binding agents or additives that are or consist primarily of non-ferrous metals; plastic and polymer-based products (including polyvinylchloride, composite building materials, and polymers used in fiber optic cables); glass (including optic glass); lumber or drywall that have been manufactured in the United States.
 - c) Installing manufactured products for which the Federal Aviation Administration (FAA) has issued a waiver as indicated by inclusion on the current FAA Nationwide Buy American Waivers Issued listing; or
 - d) Installing products listed as an Excepted Article, Material or Supply in Federal Acquisition Regulation Subpart 25.108.

By selecting this certification statement, the bidder or offeror agrees:

- a) To provide to the Airport Sponsor or FAA evidence that documents the source and origin of the steel and manufactured product.
 - b) To faithfully comply with providing U.S. domestic product.
 - c) To furnish U.S. domestic product for any waiver request that the FAA rejects.
 - d) To refrain from seeking a waiver request after establishment of the contract, unless extenuating circumstances emerge that the FAA determines justified.
- ☐ The bidder or offeror hereby certifies it cannot comply with the 100 percent Buy American Preferences of 49 USC § 50101(a) but may qualify for a Type 3 waiver under 49 USC § 50101(b). By selecting this certification statement, the apparent bidder or offeror with the apparent low bid agrees:

- a) To submit to the Airport Sponsor or FAA within 15 calendar days of being selected as the responsive bidder, a formal waiver request and required documentation that supports the type of waiver being requested.
- b) That failure to submit the required documentation within the specified timeframe is cause for a non-responsive determination that may result in rejection of the proposal.
- c) To faithfully comply with providing U.S. domestic products at or above the approved U.S. domestic content percentage as approved by the FAA.
- d) To refrain from seeking a waiver request after establishment of the contract, unless extenuating circumstances emerge that the FAA determines justified.

Required Documentation

Type 2 Waiver (Nonavailability) - The iron, steel, manufactured goods or construction materials are not available in sufficient quantity or quality in the United States. The required documentation for the Nonavailability waiver is:

- a) Completed Content Percentage Worksheet and Final Assembly Questionnaire
- b) Record of thorough market research, consideration where appropriate of qualifying alternate items, products, or materials including;
- c) A description of the market research activities and methods used to identify domestically manufactured items capable of satisfying the requirement, including the timing of the research and conclusions reached on the availability of sources.

Type 3 Waiver – The cost of the item components and subcomponents produced in the United States is more than 60 percent of the cost of all components and subcomponents of the “item”. The required documentation for a Type 3 waiver is:

- a) Completed Content Percentage Worksheet and Final Assembly Questionnaire including;
- b) Listing of all product components and subcomponents that are not comprised of 100 percent U.S. domestic content (Excludes products listed on the FAA Nationwide Buy American Waivers Issued listing and products excluded by Federal Acquisition Regulation Subpart 25.108 (products of unknown origin must be considered as non-domestic products in their entirety).
- c) Cost of non-domestic components and subcomponents, excluding labor costs associated with final assembly at place of manufacture.
- d) Percentage of non-domestic component and subcomponent cost as compared to total “item” component and subcomponent costs, excluding labor costs associated with final assembly at place of manufacture.

Type 4 Waiver (Unreasonable Costs) - Applying this provision for iron, steel, manufactured goods or construction materials, would increase the cost of the overall project by more than 25 percent. The required documentation for this waiver is:

- a) Completed Content Percentage Worksheet and Final Assembly Questionnaire from
- b) At minimum two comparable equal bidders and/or offerors;
- c) Receipt or record that demonstrates that supplier scouting called for in Executive Order 14005, indicates that no domestic source exists for the project and/or component;
- d) Completed waiver applications for each comparable bid and/or offer.

False Statements: Per 49 USC § 47126, this certification concerns a matter within the jurisdiction of the Federal Aviation Administration and the making of a false, fictitious, or fraudulent certification may render the maker subject to prosecution under Title 18, United States Code.

 Date

 Signature

 Company Name

 Title

Title VI Solicitation Notice:

The Gerald R. Ford International Airport Authority in accordance with the provisions of Title VI of the Civil Rights Act of 1964 (78 Stat. 252, 42 USC §§ 2000d to 2000d-4) and the Regulations, hereby notifies all bidders or offerors that it will affirmatively ensure that for any contract entered into pursuant to this advertisement, [select businesses, or disadvantaged business enterprises or airport concession disadvantaged business enterprises] will be afforded full and fair opportunity to submit bids in response to this invitation and no businesses will be discriminated against on the grounds of race, color, national origin (including limited English proficiency), creed, sex (including sexual orientation and gender identity), age, or disability in consideration for an award.

CERTIFICATION OF OFFEROR/BIDDER REGARDING DEBARMENT

By submitting a bid/proposal under this solicitation, the bidder or offeror certifies that neither it nor its principals are presently debarred or suspended by any Federal department or agency from participation in this transaction.

CERTIFICATION OF LOWER TIER CONTRACTORS REGARDING DEBARMENT

The successful bidder, by administering each lower tier subcontract that exceeds \$25,000 as a "covered transaction", must confirm each lower tier participant of a "covered transaction" under the project is not presently debarred or otherwise disqualified from participation in this federally-assisted project. The successful bidder will accomplish this by:

1. Checking the System for Award Management at website: <http://www.sam.gov>.
2. Collecting a certification statement similar to the Certification of Offeror /Bidder Regarding Debarment, above.
3. Inserting a clause or condition in the covered transaction with the lower tier contract.

If the Federal Aviation Administration later determines that a lower tier participant failed to disclose to a higher tier participant that it was excluded or disqualified at the time it entered the covered transaction, the FAA may pursue any available remedies, including suspension and debarment of the non-compliant participant.

DISADVANTAGED BUSINESS ENTERPRISE

Bid Information Submitted as a matter of **responsiveness**: The Owner's award of this contract is conditioned upon Bidder or Offeror satisfying the good faith effort requirements of 49 CFR § 26.53.

As a condition of responsiveness, the Bidder or Offeror must submit the following information with its proposal on the forms provided herein:

- 1) The names and addresses of Disadvantaged Business Enterprise (DBE) firms that will participate in the contract;
- 2) A description of the work that each DBE firm will perform;
- 3) The dollar amount of the participation of each DBE firm listed under (1);
- 4) Written statement from Bidder or Offeror that attests their commitment to use the DBE firm(s) listed under (1) to meet the Owner's project goal
- 5) Written confirmation from each listed DBE firm that it is participating in the contract in the kind and amount of work provided in the prime contractor's commitment; and
- 6) If Bidder or Offeror cannot meet the advertised project DBE goal, evidence of good faith efforts undertaken by the Bidder or Offeror as described in appendix A to 49 CFR part 26. The documentation of good faith efforts must include copies of each DBE and non-DBE subcontractor quote submitted to the bidder when a non-DBE subcontractor was selected over a DBE for work on the contract.

Bid Information submitted as a matter of **responsibility**:

The Owner's award of this contract is conditioned upon Bidder or Offeror satisfying the good faith effort requirements of 49 CFR § 26.53.

As a condition of responsibility, every Bidder or Offeror must submit the following information on the forms provided herein within five days after bid opening.

- 1) The names and addresses of Disadvantaged Business Enterprise (DBE) firms that will participate in the contract;
- 2) A description of the work that each DBE firm will perform;
- 3) The dollar amount of the participation of each DBE firm listed under (1);
- 4) Written statement from Bidder or Offeror that attests their commitment to use the DBE firm(s) listed under (1) to meet the Owner's project goal;
- 5) Written confirmation from each listed DBE firm that it is participating in the contract in the kind and amount of work provided in the prime contractor's commitment; and
- 6) If Bidder or Offeror cannot meet the advertised project DBE goal, evidence of good faith efforts undertaken by the Bidder or Offeror as described in appendix A to 49 CFR part 26. The documentation of good faith efforts must include copies of each DBE and non-DBE subcontractor quote submitted to the bidder when a non-DBE subcontractor was selected over a DBE for work on the contract.

FEDERAL FAIR LABOR STANDARDS ACT (FEDERAL MINIMUM WAGE)

All contracts and subcontracts that result from this solicitation incorporate by reference the provisions of 29 CFR part 201, et seq, the Federal Fair Labor Standards Act (FLSA), with the same force and effect as if given in full text. The FLSA sets minimum wage, overtime pay, recordkeeping, and child labor standards for full and part-time workers.

The [Contractor | Consultant] has full responsibility to monitor compliance to the referenced statute or regulation. The [Contractor | Consultant] must address any claims or disputes that arise from this requirement directly with the U.S. Department of Labor – Wage and Hour Division.

TRADE RESTRICTION CERTIFICATION

By submission of an offer, the Offeror certifies that with respect to this solicitation and any resultant contract, the Offeror –

- 1) is not owned or controlled by one or more citizens of a foreign country included in the list of countries that discriminate against U.S. firms as published by the Office of the United States Trade Representative (USTR);
- 2) has not knowingly entered into any contract or subcontract for this project with a person that is a citizen or national of a foreign country included on the list of countries that discriminate against U.S. firms as published by the USTR; and
- 3) has not entered into any subcontract for any product to be used on the Federal project that is produced in a foreign country included on the list of countries that discriminate against U.S. firms published by the USTR.

This certification concerns a matter within the jurisdiction of an agency of the United States of America and the making of a false, fictitious, or fraudulent certification may render the maker subject to prosecution under Title 18 USC § 1001.

The Offeror/Contractor must provide immediate written notice to the Owner if the Offeror/Contractor learns that its certification or that of a subcontractor was erroneous when submitted or has become erroneous by reason of changed circumstances. The Contractor must require subcontractors provide immediate written notice to the Contractor if at any time it learns that its certification was erroneous by reason of changed circumstances.

Unless the restrictions of this clause are waived by the Secretary of Transportation in accordance with 49 CFR § 30.17, no contract shall be awarded to an Offeror or subcontractor:

- 1) who is owned or controlled by one or more citizens or nationals of a foreign country included on the list of countries that discriminate against U.S. firms published by the USTR; or
- 2) whose subcontractors are owned or controlled by one or more citizens or nationals of a foreign country on such USTR list; or
- 3) who incorporates in the public works project any product of a foreign country on such USTR list.

Nothing contained in the foregoing shall be construed to require establishment of a system of records in order to render, in good faith, the certification required by this provision. The knowledge and information of a contractor is not required to exceed that which is normally possessed by a prudent person in the ordinary course of business dealings.

The Offeror agrees that, if awarded a contract resulting from this solicitation, it will incorporate this provision for certification without modification in all lower tier subcontracts. The Contractor may rely on the certification of a prospective subcontractor that it is not a firm from a foreign country included on the list of countries that discriminate against U.S. firms as published by USTR, unless the Offeror has knowledge that the certification is erroneous.

This certification is a material representation of fact upon which reliance was placed when making an award. If it is later determined that the Contractor or subcontractor knowingly rendered an erroneous certification, the Federal Aviation Administration (FAA) may direct through the Owner cancellation of the contract or subcontract for default at no cost to the Owner or the FAA.

CERTIFICATION REGARDING LOBBYING

The Bidder or Offeror certifies by signing and submitting this bid or proposal, to the best of his or her knowledge and belief, that:

- (1) No Federal appropriated funds have been paid or will be paid, by or on behalf of the Bidder or Offeror, to any person for influencing or attempting to influence an officer or employee of an agency, a Member of Congress, an officer or employee of Congress, or an employee of a Member of Congress in connection with the awarding of any Federal contract, the making of any Federal grant, the making of any Federal loan, the entering into of any cooperative agreement, and the extension, continuation, renewal, amendment, or modification of any Federal contract, grant, loan, or cooperative agreement.
- (2) If any funds other than Federal appropriated funds have been paid or will be paid to any person for influencing or attempting to influence an officer or employee of any agency, a Member of Congress, an officer or employee of Congress, or an employee of a Member of Congress in connection with this Federal contract, grant, loan, or cooperative agreement, the undersigned shall complete and submit Standard Form-LLL, "Disclosure Form to Report Lobbying," in accordance with its instructions.
- (3) The undersigned shall require that the language of this certification be included in the award documents for all sub-awards at all tiers (including subcontracts, subgrants, and contracts under grants, loans, and cooperative agreements) and that all sub-recipients shall certify and disclose accordingly.

This certification is a material representation of fact upon which reliance was placed when this transaction was made or entered into. Submission of this certification is a prerequisite for making or entering into this transaction imposed by section 1352, title 31, U.S. Code. Any person who fails to file the required certification shall be subject to a civil penalty of not less than \$10,000 and not more than \$100,000 for each such failure.

PROCUREMENT OF RECOVERED MATERIALS

Contractor and subcontractor agree to comply with Section 6002 of the Solid Waste Disposal Act, as amended by the Resource Conservation and Recovery Act, and the regulatory provisions of 40 CFR Part 247. In the performance of this contract and to the extent practicable, the Contractor and subcontractors are to use products containing the highest percentage of recovered materials for items designated by the Environmental Protection Agency (EPA) under 40 CFR Part 247 whenever:

- 1) The contract requires procurement of \$10,000 or more of a designated item during the fiscal year; or
- 2) The contractor has procured \$10,000 or more of a designated item using Federal funding during the previous fiscal year.

The list of EPA-designated items is available at www.epa.gov/smm/comprehensive-procurement-guidelines-construction-products.

Section 6002(c) establishes exceptions to the preference for recovery of EPA-designated products if the contractor can demonstrate the item is:

- a) Not reasonably available within a timeframe providing for compliance with the contract performance schedule;
- b) Fails to meet reasonable contract performance requirements; or
- c) Is only available at an unreasonable price.